

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6254-55)

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 22, 23, 26, and 27,, with brass cap marked

T29S	R2W
S22	S23
S27	S26
1917	

from which

- A Fir 36" dia bears N.50°30'E., 33 lks mkd T29S R2W S23 BT
- A Cedar 12" dia. bears S.31°E., 56 lks mkd T29S R2W S26 BT
- A Fir 14" dia. bears S.21°30'W. 55 lks mkd T29S R2W S27 BT
- A Cedar 10" dia. bears N.48°W., 16 lks mkd T29S R2W S22 BT

BLM Dependent resurvey by Joseph M Mannix, Cadastral Surveyor and Justin V Haddon, Cadastral Surveyor under Group No. 2957, surveyed Oct/Nov. 2019 - (DCSO records Vol. 59 Pg(s) 23936-7)

The cor. of secs. 22, 23, 26, and 27, monumented with the original iron post, 2" dia., firmly set, projecting 18" above ground, with a brass cap (properly) mkd.

from which the remains of the original bearing trees

- A fir snag, 42" dia., bears N.50½°E., 21.8 ft., with a healed blaze.
- A decayed fir stump, size indeterminate, bears S.21½°W., 36.3 ft., no marks visible.
- A cedar, 21" dia., bears N.48°W., 10.6 ft., with a healed blaze.

and new bearing trees

- A cedar, 19" dia., bears N.67¾°E., 12.5 ft., mkd. T29S R2W S23 BT.
- A fir, 11" dia., bears S.27¾°E., 21.2 ft., mkd. T29S R2W S26 BT.
- A fir, 7" dia., bears S.15½°W., 19.7 ft., mkd. T29S R2W S27 BT.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. angle iron driven alongside each monument.

NAD 1983 (2011):

Latitude: 43°02'01.73" N. Longitude: 122°55'19.88" W.