

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GL0 resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6256)

Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for 1/4 sec. cor., with brass cap marked

1/4
S22 | S23
1917

from which

A Pine 40" dia., bears S.73°30'E., 28 lks. dist. mkd. 1/4 S23 BT.

A Fir 24" dia., bears N.52°45'W., 21 lks. dist. mkd. 1/4 S22 BT.

This cor. is 1.00 ch. E. of the top of a ridge, which bears N. and S.

BLM Dependent resurvey by Joseph M Mannix, Cadastral Surveyor and Justin V Haddon, Cadastral Surveyor under Group No. 2957, surveyed Oct/Nov. 2019 - (DCSO records Vol. 59 Page(s) 23937)

The 1/4 sec cor. of secs. 22 and 23, monumented with the original iron post, 1" dia., firmly set, projecting 12" above ground with a brass cap (properly) mkd.

from which the remains of an original bearing tree

A decayed fir stump, size indeterminate, bears N.52 3/4°W., 13.9 ft., no marks visible.

and new bearing trees

A fir, 9" dia., bears N.59°E., 22.5 ft., mkd. 1/4 S23 BT.

A fir, 22" dia., bears N.45 1/2°W., 32.9 ft., mkd. 1/4 S22 BT.

Each new BT has a 2 1/2" x 1/4" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.