

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCS0 records Vol. 15 Page(s) 6256)

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 14, 15, 22 and 23,, with brass cap marked

T29S R2W
S15 | S14

S22 | S23
1917

from which

- A Fir 20" dia., bears N.58°45'E., 73 lks. dist. mkd. T29S R2W S14 BT.
- A Cedar 30" dia., bears S.41°30'E., 30 lks. dist. mkd. T29S R2W S23 BT.
- A Fir 12" dia., bears S.60°W., 11 lks. dist. mkd. T29S R2W S22 BT.
- A Fir 18" dia., bears N.38°45'W., 63 lks. dist. mkd. T29S R2W S15 BT.

BLM Dependent resurvey by Joseph M Mannix, Cadastral Surveyor and Justin V Haddon, Cadastral Surveyor under Group No. 2957, surveyed Oct/Nov. 2019 - (DCS0 records Vol. 59 Pages 23937-8)

The cor. of secs. 14, 15, 22, and 23, monumented with the original iron post, 2" dia., firmly set, projecting 3" above ground, with a brass cap (properly) mkd.

from which the remains of the original bearing trees

- A fir, 27" dia., bears N.58¾°E., 48.2 ft., with a healed blaze.
- A cedar snag, 31" dia., bears S.41½°E., 19.8 ft., no marks visible.
- A fir, 31" dia., bears N.38¾°W., 41.6 ft., with a healed blaze.

and new bearing trees

- A cedar, 13" dia., bears S.14¼°E., 40.9 ft., mkd. T29S R2W S23 BT.
- A fir, 18" dia., bears S.10¼°W., 49.3 ft., mkd. T29S R2W S22 BT.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.