

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6257-58)

-----  
Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for 1/4 sec. cor., with brass cap marked

$\frac{1}{4}$   
S15 | S14  
1917

from which

- A Fir 24" dia., bears S.63°E, 44 lks. dist. mkd.  $\frac{1}{4}$  S14 BT
- A Fir 22" dia., bears S.64°30'W., 27 lks. dist. mkd.  $\frac{1}{4}$  S15 BT.

BLM Dependent resurvey by Joseph M Mannix, Cadastral Surveyor and Justin V Haddon, Cadastral Surveyor under Group No. 2957, surveyed Oct/Nov. 2019 - (DCSO records Vol. 59 Page(s) 23942)

-----  
The  $\frac{1}{4}$  sec. cor. of secs. 14 and 15, monumented with the original iron post, 1" dia., firmly set, projecting 10" above ground, with a brass cap mkd.  $\frac{1}{4}$  S14 S15 1917,

from which the remains of the original bearing trees

- A fir stump, 27" dia., bears S.60 $\frac{1}{4}$ °E., 29.0 ft., with a healed blaze. (Record, S.63°E.)
- A fir stump 29" dia., bears S.59 $\frac{1}{2}$ °W., 17.8 ft., with a healed blaze. (Record, S.64 $\frac{1}{2}$ °W.)

At the corner point Add marks to the brass cap to now read  
T 29 S R 2 W

$\frac{1}{4}$   
S 15 | S 14  
2019  
1917

and new bearing trees

- A fir, 10" dia., bears N.44°E., 22.8 ft., mkd.  $\frac{1}{4}$  S14 BT.
- A fir, 8" dia., bears N.85 $\frac{1}{4}$ °W., 10.2 ft., mkd.  $\frac{1}{4}$  S15 BT.