

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6260)

-----  
Set an iron post 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 2, 3, 10 and 11, with brass cap marked:

T29S R2W  
S3|S2  
S10|S11  
1917

from which

- A Fir 16" dia., bears N.50°30'E., 26 lks. dist. mkd. T29S R2W S2 BT.
- A Fir 10" dia., bears S.28°E., 35 lks. dist. mkd. T29S R2W S11 BT.
- A Fir 12" dia., bears S.74°W., 13 lks. dist. mkd. T29S R2W S10 BT.
- A Pine 6" dia., bears N.17°W., 27 lks. dist. mkd. T29S R2W S3 BT.

Dennis Gaylord, U.S.F.S. (Deputized by the County) - Wit:  
Randal Lopez - March 30, 1978 - C.S. File 59/46-51

-----  
Found - 1917 GLO brass cap on a 1½" I.P. set firmly in ground and properly stamped.

- 12" Sugar Pine, orig. 6", bears N.17°W., 17.3 ft. (Rec. 17.82 ft.) Has a healed scar.
- 21" D.Fir, orig. 12", bears S.68°W., to center of tree, (Rec. S.74°W.) 8.58 ft. Has a healed scar.
- 11" D.Fir, orig. 10", bears S.29°E., 22.9 ft. (Rec. S.28°E. 23.1 ft.) Has a healed scar.
- A 21" D.Fir, orig. 16", bears N.51°30'E., 16.2 ft. (Rec. N.50°30'E., 17.2 ft., slope dist. is 17.2 ft.) Has a healed scar.

Placed County BT signs on all BTs.

No new monument set or new accessories.