

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3 only, (North)

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6239)

Set a porphyry stone, 18x10x8 ins., 12" in the ground for cor. of secs. 2 and 3, marked with 4 notches on the W. and 2 notches on E. edge; from which

A Pine 14" dia., bears S.78°E., 45 lks. dist., mkd. T29S R2W S2 BT.

A Fir 14" dia., bears S.36°W., 19 lks. dist., mkd. T29S R2W S3 BT.

Douglas Co. Surveyors Office - Dennis Gaylord, U.S.F.S. (Deputized by the County) Wit: Randal Lopez - March 9, 1978 -C.S. File 59/46-53

Found - Orig. 14" now 17" Fir stump bears S.40°W., 12.54 ft. (Rec. S.36°W.) has a healed scar.

Orig. 14" now 16" Pine stump bears S.79°E., 29.70 ft. (Rec. S.78°E.) Scribing visible on unhealed blaze "T29S R2W S2 BT"

Using record distances and bearing tree stumps, at the intersect point, I SET a 2½" brass cap on a 1" Galv. I.Pipe stamped: County Surveyors Office

T 28 S	
S 34	R
S 3 S 2	2
T 29 S	W
1978	

New BTs- 16" D.Fir bears S.10°E., 144.4 ft. scribed "T29S R2W S2 CS BT" on a double blaze.

22" D.Fir bears S.37°30'W., 115.8 ft. scribed "T29S R2W S3 CS BT" on a double blaze.

Placed County BT signs on all BTs and stumps.

Corner lies 50 ft. North of Road #274 in a clearcut unit.

Douglas Co. Surveyor's Office - Crew: Stephen J Flause & Jeffery Lorsung - 10/9/2018 - C.S. File 67/45-24

Found - A 1" I.D. iron pipe, firmly set, projecting 13" above the ground in a 18" dia. stone collar by Gaylord in 1978 with a 2½" dia brass cap (properly) mkd.

Original BT by Strickler in 1917:

A rotted and tipped out pine bears, S.79°E., 29.7 ft. to center of the roothole.

Continued next page

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3 only, (North)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

BTs by Gaylord in 1978:

A 25" D.Fir bears, S.10°E., 144.4 ft. with a healed blaze.

A 29" D.Fir bears, S.37°30'W., 115.8 ft with a healed blaze.

A 17"x5' D.Fir stump bears, S.40°W., 12.5 ft. with healed blaze.

New BTs- A 11" D.Fir bears N.60°E., 14.5 ft. scribed "T28S R2W S34", "CS BT"

A 9" D.Fir bears N.82½°W., 28.6 ft. scribed "T28S R2W S34", "CS BT".

LOCATION & COMMENTS:

All BTs have BT tags attached. All new BTs have double blazed faces with bearings measured to the center of the tree at the root crown and distances measured to a 2½" PK nail in the side and center of the root crown.

The corner monument is approximately 50 ft. North of National Forest Road 2810.

GEODETIC COORDINATES

N 525,821.63 E 4,274,404.10

LATITUDE: 43°05'01.717" N. LONGITUDE: 122°55'18.585" W.

DATUM: NAD 83, Epoch 2010.00 SOURCE: Trimble GeoXT 6000

COMPASS DECLINATION: 15°E.