

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only, T28-2

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5433)

-----  
Set granite stone 5 x 14 x 16 ins., 11" in the ground for cor. secs. 34 and 35, marked with 4 notches on W. and 2 notches on E. edge, and raise mound of stone 2 ft. base, 1½ ft. high, W. of cor., from which  
A Chinquapin 8" dia., bears N.49°30'W., 33 lks. dist., mkd. T28S R2W S34 BT.  
No other tree fit to mark.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6239-40)

-----  
The Sec. cor. of 34 and 35, T28S R2W only, which is a granite stone, firmly set, marked and witnessed as described by the surveyor general. I re-witness this cor., as follows: from cor.  
A Fir 24" dia., bears N.73°45'E., 36 lks. dist., marked T28S R2W S35 BT. (New BT)  
A Chinquapin 8" dia., bears N.49°30'W., 33 lks. dist., marked T28S R2W S34 BT (Old BT)

Found and used in GLO survey Fred Mensch, U.S. Deputy Surveyor - under Special Instructions dated June 7, 1922 (DCSO records Vol. 13 Page(s) 5493)

Douglas Co. Surveyors Office - Dennis Gaylord, U.S.F.S. (Deputized by the County) Wit: Randal Lopez - April 13, 1978 - C.S. File 59/46-48

-----  
Found - Orig. corner stone 16"x14"x5", set firmly in the ground. Stone is marked with 2 grooves on the E. edge and 4 grooves on the W. edge.  
32" D.Fir bears N.75°E., 23.76 ft. (Rec. N.73°45'E.) has a healed scar.  
6" Chinquapin is down. Stump bears N.50°W., 21.4 ft. (Rec. N.49°30'W., 21.78 ft.) Scribing visible on Chinquapin log, "T28S R2W S34 BT"  
Placed BT signs on both BTs.  
Moving the corner stone aside, I SET in its place a 2½" brass cap on a 1" I.P. stamped: County Surveyors Office 1978  
T 28 S R 2 W  
S 34 S 35  
(Cont. Next Page)

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 536700

PRIMARY CORNER DESCRIPTION So. Sec. Cor. for 34 & 35 only, T28-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

I bury corner stone alongside iron pipe.  
New BT - 17" D.Fir bears N.5°W., 44.4 ft. scribed "T28S R2W  
S34 CS BT" on a double blaze. Placed a county BT  
sign on Fir.