

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 540700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 2 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6240)

Set an iron post 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor. of sec. 2 only, with brass cap mkd.

1/4 S2
1917

from which

A Chinquapin 10" dia., bears S.59°E., 25 lks. dist., mkd. 1/4 S2 BT.

A Fir 10" dia., bears S.74°W., 26 lks. dist. mkd. 1/4 S2 BT.

Found and used in GLO survey by Fred Mensch under Special Instructions dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5493-94)

Douglas Co. Surveyors Office - Dennis Gaylord, U.S.F.S. (Deputized by the County) Wit: Randal Lopez - April 13, 1978 - C.S. File 59/46-42

Found - 2 1/2" brass cap stamped U.S. General land Office Survey 1/4 S2 1917, on a 1" I.P., set solidly 12" above ground. I ADD "T29S R2W" to brass cap below the "S2".

15" D.Fir bears S.73°30'W., 17.16 ft. (Rec. S.74°W.) Has a healed scar.

8" Chinquapin is down, stump bears S.57°30'E., 17.0 ft. (Rec. S.59°E., 16.5 ft.) Scribing visible on down log "1/4 S"

Placed BT sign on Fir and Chinquapin log.

No new monument set.

New BT - 16" D.Fir bears S.35°E., 28.7 ft. scribed "1/4 S2 CS BT" on a double blaze. Placed a county BT sign on Fir.