TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 541100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 2 only, T30-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 15 Page(s) 6198) (Duplicate Pg. 6822)

Set a basalt stone 16x9x6 ins., 11" in the ground for ¼ sec. cor. marked ¼ on N. face, from which

A Sugar Pine 28" dia., bears N.56°E., 20 lks. dist. mkd. ¼ S35 BT.

A Fir 20" dia., bears S.84°E., 37 lks. dist. mkd. ¼ S2 BT.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6215)

Intersect the ¼ sec. cor., which is a basalt stone, firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to sec. 2, T30S R2W only by destroying all marks referring to sec. 35 and marking ¼ on S. face, From cor.

A Hemlock 8" dia., bears S.63°W., 73 lks. dist. mkd. ¼ S2 BT. (New BT)

A Fir 20" dia., bears S.84°E., 37 lks. dist. mkd. ¼ S2 BT. (Old BT)

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Oct/Nov. 1968 - C.S. File 54/73-25

Found - 20" D.Fir, now stump, S.84°E., 24.4 ft., opened for scribing.
No trace of corner stone nor SE. bearing tree.

Set Brass cap at cor. mkd: County Surveyors Office
T 29 S
T 30 S R2W ¼ S 2
1968

New BTs- 10" Hemlock S.22°E., 15.8 ft. mkd. ¼ S2 CS BT.
10" Hemlock S.72°W., 48.4 ft. mkd. ¼ S2 CS BT.

This corner lies 39.1 ft. East of ¼ cor. Sec. 35, T29-2.

Survey by Loyd R. Moffit, LS. #944 - For: U.S. Forest Service Oct. 1986 - C.S. File 62/30-10

Found - 1968 DCSO brass cap on a 1" I.P. in a rock mound.
16" Hemlock bears S.22°E., 15.8 ft., scar visible.
Fir stump bears S.84°E., 34.4 ft. scribe visible

New BT - I scribed a 6" Fir which bears S.41¼°E., 35.2 ft. mkd. "¼ S2 BT" with LS 944 brass washer nailed to BT scribe.