

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 576700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 35 only, T28-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6240)

-----  
Set a basalt stone 20x8x5 ins., 15" in the ground for ¼ cor. of sec. 35, T28S R2W only, marked ¼ on N. face, from which  
A Fir 10" dia., bears N.25°15'E., 25 lks. dist. mkd. ¼ S35 BT.  
A Pine 12" dia., bears N.36°15'W., 43 lks. dist., mkd. ¼ S35 BT.

GLO resurvey by Fred Mensch, under Special Instructions dated June 7, 1923 - (DCSO records Vol. 13 Page(s) 5492)

-----  
(37.09 chains)  
The cor. established for ¼ sec. cor. of sec. 35, which is a basalt stone, 15x8x5 ins. set, marked, and witnessed as described. I destroy this corner.  
(West)  
(40.00 chains)  
Set an iron post 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor. of sec. 35 only, with brass cap mkd.  $\frac{1}{4} S 35$   
1923  
from which  
A Fir 12" dia., bears N.89°E., 20 lks. dist. mkd. ¼ S35 BT.  
A Fir 12" dia., bears N.23°W., 3 lks. dist. mkd. ¼ S35 BT.

Douglas Co. Surveyors Office - Dennis Gaylord, U.S.F.S. (Deputized by the County) - Wit: Randal Lopez - March 23, 1978 - C.S. File 59/46-47

-----  
Found - 2½" brass cap on 1" I.P. stamped U.S. General Land office Survey 1/4 S35 1923. I ADD "T28S R2W" to brass cap above the 1/4 S35.  
16" D.Fir bears N.23°W., 1.98 ft. Has a healed blaze.  
17" D.Fir bears N.89°E., 13.8 ft. (Rec. 13.2 ft.) Has a healed blaze.  
Placed County BT signs on both trees.  
Did not remonument or add accessories.