

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 35 & 36 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6215)

Set a basalt stone 18x12x6 ins., 12" in the ground for cor. of secs. 35 and 36, marked with 1 notch on E. and 5 notches on W. edge; from which
A Fir 30" dia., bears N.45°30'E., 19 lks. dist., mkd. T29S R2W S36 BT.
A Fir 15" dia., bears N.47°W., 58 lks. dist. mkd. T29S R2W S35 BT.

Douglas Co. Surveyors Office - John M. Powell; Jack Heritage; W. Penley, crew - Nov. 1968 - C.S. File 54/73-26

Found - Stone approx. size, at corner but no marks found. 30" D.Fir, now down, N.45½°E., 12.5 ft. scribe visible.

No trace of NW. BT.

Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R2W ¼ S35 | S36
T 30 S
1968

New BTs- 24" D.Fir, North 38.0 ft. mkd. T29S R2W S36 CS BT
20" D.Fir N.10°W., 25.7 ft. mkd. T29S R2W S35 CS BT
8" W.Fir S.24°W., 18.6 ft. mkd. T30S R2W S2 CS BT.

Survey by Glenn Baughman - For: U.S. Forest Service - April 1979 - C.S. File 58/176-30

Found - 1" Iron pipe with 1968 county brass cap.
10" W.Fir S.24°W., 18.6 ft.
20" D.Fir N.10°W., 25.7 ft.
24" D.Fir, snag, North, 38.0 ft.
30" D.Fir, down, N.45½°E., 12.5 ft.
New BT- Marked a 6" W.Fir N.24°E., 31.1 ft. "S36 BT" and attached brass washer stamped "Land Surveyor 536" on lower face.

Fd. & used on BLM dependent resurvey by Wayne Rogers, Cadastral Surveyor and Robert Browning, under Group #1883 surveyed June/July 1998 - (DCSO recs. Vol. 53 Pg(s) 20332-3)