

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 674700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 36 only, T28-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6242)

Set a basalt stone 18x12x10 ins., 12" in the ground for ¼ sec. cor. of sec. 36, T28S R2W only, marked ¼ on N. face, from which

A Fir 30" dia., bears N.22°45'E., 51 lks. dist. mkd. ¼ S36 BT.

A Fir 24" dia., bears N.21°W., 56 lks. dist., mkd. ¼ S36 BT.

GLO resurvey by Fred Mensch, under Special Instructions dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5491)

(3.62 chs.)

The ¼ sec. cor., established for sec. 36, which is a basalt stone, marked and witnessed as described by the surveyor general. I destroy this corner.

(West)

(6.53 chs.)

Set an iron post 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor. of sec. 36 only, with brass cap mkd: ¼ S 36
1923

from which

A Hemlock 14" dia., bears N.20°E., 19 lks. dist., mkd. ¼ S36 BT.

A Cedar 16" dia., bears N.67°W., 42 lks. dist., mkd. ¼ S36 BT.

Douglas Co. Surveyors Office - Dennis Gaylord, U.S.F.S. (Deputized by the County) Wit: Randal Lopez - March 16, 1978 - C.S. File 59/46-54

Found - 2½" 1923 GLO brass cap on ¾" I.P. set solidly in ground. Brass cap stamped U.S. General Land office Survey 1/4 S36 1923. I ADD "T28S R2W" to brass cap above the "¼ S36".

A 51" Fir stump with a railroad spike in top. Spike bears N.52°W., 10.1 ft. (Not of record)

A 45" Cedar stump with a railroad spike in top. Spike bears N.9°30'W., 14.7 ft. (Not of record)

No trace remains of original BTs.

No new monument or accessories.

Placed County BT signs on both stumps. Corner n a clearcut unit. No tres near by.