

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6206)

Set an iron post 3 ft. long, 1" dia., 26" in the ground for 1/4 cor. of sec. 36 only, with brass cap mkd:

1/4 |
S36 |
1917

from which

A Pine 48" dia., bears S.88°30'W., 61 lks. dist., mkd. 1/4 S36 BT.

A Fir 14" dia., bears N.24°30'W., 79 lks. dist. mkd. 1/4 S36 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - July 25, 1969 - C.S. File 54/82-33

Found - 14" D.Fir now 18", N.24½°W., 52.1 ft., scribe visible "B".

GLO brass cap, properly mkd. in 1917, at 1/4 cor.

48" Pine now snag, S.88½°W., 40.3 ft. scribe visible.

New BT - 7" D.Fir S.75°W., 7.2 ft. scribed 1/4 S36 CS BT.

This cor. lies 23.8 ft. North of 1/4 cor. for Sec. 31, T29-1.

Fd. and used in BLM resurvey by Donovan C. Harris, Cadastral Surveyor, under Group #748, surveyed Aug. 3-5, 1971 - (DCSO records Vol. 35 Page(s) 14586)