

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 only (East)

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6206)

-----

Set a basalt stone 18x10x7 ins., 12" in the ground, for cor. of secs. 25 and 36, marked with 5 notches on the N. and 1 notch on S. edge; from which

A Fir 10" dia., bears S.5°30'W., 21 lks. dist. mkd. T29S R2W S36 BT.

A Fir 6" dia., bears N.61°45'W., 48 lks. dist. mkd. T29S R2W S25 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - April 1969 - C.S. File 54/82-30

-----

Found - 18x10x7" basalt corner stone, properly mkd., and set at section cor. point.

10" D.Fir now 16", S.5½°W., 13.9 ft. Shows excellent scar.

6" D.Fir now 10", N.17°W., 31.7 ft. Shows excellent scar.

Place yellow tags on both BTs.

Set brass cap in place of corner stone, mkd: County Surveyors Office 1969

R	T 29	S	R
2	S 25		S30 1
W	S 36		W

Place corner stone by brass cap.

This cor. lies North 18.5 ft. from sec. cor. of 30 & 31 of T29-1.

BLM resurvey by Donovan C. Harris, Cadastral Surveyor - Group #748, surveyed Aug. 3-5, 1971 - (DCSO records Vol. 35 Page(s) 14587)

-----

The Sec. cor., perpetuated by Powell in 1969, with an iron post 1½" dia., firmly set, extending 14" above the ground with brass cap mkd. in 1969

from which original bearing trees:

A Fir 16" dia., bears S.5½°W., 21 lks. dist., mkd. with healed blaze.

A Fir 10" dia., bears N.62½°W., 27 lks. dist., mkd. with healed blaze. (Rec. N.61 3/4°W., 48 lks.)

and a bearing tree of which I have no record:

A Madrone 13" dia., bears N.32°W., 30 lks. dist., mkd. with partly healed blaze.