

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6207)

Set an iron post 3 ft. long, 1" dia., 26" in the ground for ¼ cor. of sec. 25 only, with brass cap mkd:

¼
S25
1917

from which

A Fir 24" dia., bears S.51°45'W., 40 lks. dist. mkd. ¼ S25 BT.

A Chinquapin 8" dia., bears N.28°30'W., 53 lks. dist., mkd. ¼ S25 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & crew - April 24, 1969 - C.S. File 54/82-28

Found - Brass cap in excellent condition and properly mkd. by GLO in 1917.

24" D.Fir now 29", S.52°W., 26.4 ft. Shows good scar and is good for bearing and dist.

8" Chinquapin now 9", N.28½°W., 35.0 ft. Has rotten face and shows no trace of scribing and is good for bearing and dist.

Place yellow tags on both BTs.

New BT - 6" D.Fir N.77°W., 16.4 ft. scribed ¼ S25 CS BT.

The ¼ cor. lies North 33.7 ft. from ¼ S30, T29-1.

Cor. lies on steep West side.