

PRIMARY CORNER DESCRIPTION W. Sec. Cor. for 19 & 30 only, T29-1

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #757, dated Sept. 14, 1904 - (DCSO records Vol. 14 Page(s) 6073)

 Set a basalt stone 16x12x8 ins., 11" in the ground for cor. of secs. 19, 24, 25 and 30, marked with 4 notches on N. and 2 notches on S. edge, from which
 A Cedar 12" dia., bears N.39°E., 73 lks. dist. mkd. T29S R1W S19 BT.
 A Red Fir 24" dia., bears S.51°E., 23 lks. dist. mkd. T29S R1W S30 BT.
 A Red Fir 24" dia., bears S.89°W., 85 lks. dist. mkd. T29S R2W S25 BT.
 A Yellow Pine 36" dia., bears N.74°W., 50 lks. dist. mkd. T29S R2W S24 BT.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6207-08)

 Intersect the cor. of secs. 19, 24, 25 and 30, which is a basalt stone firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to secs. 19 and 30, T29S R1W only by destroying all marks referring to secs. 24 and 25.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - July 30, 1969 - C.S. File 54/82-40

 Found - 12" Cedar now down, N.39°E., 48.2 ft. shows good scar.
 24" D.Fir S.51°E., 15.2 ft., shows good scar.
 16x12x8 ins stone, firmly set at sec. cor. mkd. 4 notches on North and 2 notches on South edges.

Set Brass cap at cor. mkd: County Surveyors Office

		T	29	S	
R	S25		S 19	R	
2			S 30	1	
W				W	
			1969		

New BTs- 6" D.Fir N.30°E., 15.2 ft. scribed T29S R1W S19 CS BT.
 10" D.Fir S.80°W., 18.1 ft. scribed T29S R2W S25 CS BT.
 This corner lies 25 ft. South of cor. for 24 & 25 only, T29-2