

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only, (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6208)

Set a basalt stone 15x12x6 ins., 10" in the ground for cor. of secs. 24 and 25, marked with 4 notches on N. and 2 notches on S. edge from which
A Pine 40" dia., bears S.61°45'W., 56 lks. dist. mkd. T29S R2W S25 BT.
A Fir 24" dia., bears N.33°30'W., 67 lks. dist. mkd. T29S R2W S24 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - April 30, 1969 - C.S. File 54/82-41

Found - 40" Pine now 49", S.61 3/4°W., 37.0 ft., shows good scar.
24" D.Fir now 28", N.33½°W., 44.2 ft., shows good scar.
15x12x6" stone mkd. 4 notches North, 2 notches on the South edges.

Set Brass cap at cor. mkd: County Surveyors Office

	T	29	S
R	S24		S19 R
2	S25		1
W			W

1969

New BT - 8" D.Fir N.68°E., 19.9 ft. scribed T29S R1W S19 CS BT.

This cor. lies 25.6 ft. North of cor. for 19 & 30, T29-1