TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 24; & S.19, T29-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #757, dated Sept. 14, 1904 - (DCSO records Vol. 13 Page(s) 6074)

Set a basalt stone 15x9x6 ins., 10" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which

A Red Fir 20" dia., bears N.20°E., 79 lks. dist. mkd. ¼ S19 BT.

A Red Fir 6" dia., bears S.65°W., 185 lks. dist. mkd. ¼ S24 BT.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6208)

Intersect the ¼ sec. cor., which is a basalt stone, firmly set, marked and witnessed as described by the surveyor general. I perpetuate this cor., as follows; alongside the old cor.

Set an iron post, 3 ft. long, 1" dia., 26" in the ground for ¼ sec. cor., with brass cap mkd:

¼
S24 | S19
1917

from which

A Red Fir 20" dia., bears N.20°E., 79 lks. dist. mkd. ¼ S19 BT. (Old BT)

A Red Fir 6" dia., bears S.65°W., 185 lks. dist. mkd. ¼ S24 BT. (Old BT)

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - July 30, 1969 - C.S. File 54/82-38

Found - 20" D.Fir now 39", N.20°E., 47.2 ft. (Rec. 52.1 ft.) Shows good scar.

6" D.Fir now 26", S.65°W., 122.1 ft., shows faint scar.

Brass cap at ¼ cor. mkd. ¼ S24 only, General Land Office, 1917. Orig. stone along side cap mkd. ¼

Remarked brass cap as follows: General Land Office

T 29 S
¼
R 2 W | S24 S19 | R 1 W

New BT - 10" Cedar S.3°W., 4.2 ft. scribed ¼ S24 CS BT.