

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19 only, T29-1

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #757, dated Sept. 14, 1904 - (DCSO records Vol. 14 Page(s) 6074)

 Set a basalt stone 20x12x10 ins., 15" in the ground for cor. of secs. 13, 18, 19 and 24, marked with 3 notches on N. and S. edges, from which
 A Sugar Pine 40" dia., bears N.8°E., 122 lks. dist. mkd. T29S R1W S18 BT.
 A Red Fir 10" dia., bears S.55°E., 123 lks. dist. mkd. T29S R1W S19 BT.
 A Red Fir 24" dia., bears S.3°W., 89 lks. dist. mkd. T29S R2W S24 BT.
 A Red Fir 6" dia., bears N.5°W., 98 lks. dist. mkd. T29S R2W S13 BT.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6209)

 Intersect the cor. of secs. 13, 18, 19 and 24, which is a basalt stone firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to secs. 18 and 19, T29S R1W only and destroy all marks referring to secs. 13 and 24.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - April 30, 1969 - C.S. File 54/82-37

 Found - 40" Pine now 52" N.11°E., 81.2 ft. Shows good scar.
 10" D.Fir now 24" S.55°E., 81.2 ft. shows scar.
 20x12x10 stone 3 notches on N. & S.

Set Brass cap at cor. mkd: County Surveyors Office

	T	29	S	
R			S 18	R
2	S24		S 19	1
W				W

1969

New BTs- 12" Cedar N.89°E., 14.8 ft. scribed T29S R1W S18 CS BT.
 17" D.Fir S.28°E., 17.0 ft. scribed T29S R1W S19 CS BT.

This cor. lies 17.8 ft. South of cor. 13 & 24 only, T29-2