

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13 only, East

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6210)

Set a basalt stone 10x20x16 ins., 15" in the ground for cor. of secs. 12 and 13, marked with 2 notches on N. and 4 notches on S. edge, from which
A Hemlock 10" dia., bears S.39°15'W., 54 lks. dist. mkd. T29S R2W S13 BT.
A Fir 36" dia., bears N.26°30'W., 70 lks. dist. mkd. T29S R2W S12 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - May 1, 1969 - C.S. File 54/82-45

Found - 10" Hemlock now 14", leaning badly S.39°W., 35.6 ft. scribe visible "R" and other marks.
36" D.Fir now 48", N.26½°W., 46.2 ft. shows good scar.
20x20x6 stone at sec. cor. mkd. 2 notches on the N. edge and 4 notches on the S.

Set Brass cap at cor. mkd: County Surveyors Office
T 29 S
R S12 | S18 R
2 S13 | 1
W 1969 W

New BT - 20" Hemlock S.73°W., 5.5 ft. scribed T29S R2W S13 CS BT.

This cor. lies 7.9 ft. South of cor. for 7 & 18, T29-1