

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION NE. Cor. Sec. 1 (NE. Twp. Cor.)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6212-13)

-----  
Set an iron post 3 ft. long, 3" dia., 24" in the ground for the NE. cor. of T. 29 S., R. 2 W., with brass cap marked:

-----  
S1  
T29S  
R2W  
1917

from which

A Fir 14" dia., bears S.35°W., 14 lks. dist., mkd. T29S R2W S1 BT.

GLO survey by Fred Mensch, under Special Instructions dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6155-56)

-----  
The NE. cor. of T29S R2W, which is a 3" Iron post, firmly set, marked and witnessed as described by the surveyor general. I change this cor. to cor. of Tps. 29S., Rs. 1 and 2 W., and mark an additional bearing tree. The cor. is now marked and witnessed as follows: T28SR2WS36

-----  
S1 | S6  
T29S | T29S  
R2W | R1W  
1917

from which

A Fir 12" dia., bears S.66°E., 46 lks. dist., marked T29S R1W S6 BT. (New BT)

A Fir 14" dia., bears S.35°W., 14 lks. dist., marked T29S R2W S1 BT. (Old BT)

Douglas Co. Surveyors Office - Dennis Gaylord, U.S.F.S. (Deputized by the County) Wit: Randal Lopez - March 16, 1978 - C.S. File 59/46-55

-----  
Found - 1917 GLO brass cap on 3" I.P., solidly set in ground and properly stamped.

18" D.Fir stump with a healed blaze bears S.35°W., 9.24 ft.

14" D.Fir stump with healed blaze bears S.66°E., 31.8 ft. (Rec. 30.36 ft.)

New Bearing objects:

3/4" Iron rod set in a 20" Cedar stump, 1" alum. cap stamped R.M. 11.2' and arrow, on iron rod, bears N.58°W., 11.2 ft.

(Cont. Next Page)

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION NE. Cor. Sec. 1 (NE. Tsp. Cor.)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

3/4" Iron rod with 1" alum. cap stamped R.M. 39.0'  
with arrow, set in a 19" D.Fir stump bears  
S.88°E., 11.2 ft.  
Placed County BT signs on all 4 stumps. Corner in a clear-  
cut unit. No trees nearby.