

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 974030

PRIMARY CORNER DESCRIPTION Cor. No. 1, H.E.S. #140

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Homestead Entry Survey executed by Frank D. Maxwell, Forest Service, under Special Instructions dated April 27, 1914 - (DCSO records Vol. 27 Page(s) 11741)

-----

At Cor. No. 1, identical with Cor. H/1 of listing survey, a post, mkd. and witnessed as described by Asher Ireland, Asst. Forest Ranger, in place of which I set an igneous stone, 14 x 16 x 6 ins., 14" in the ground for Cor. No. 1, mkd. 1 h E S 140 on NW. face, with a cross (X) on top; from which

A Fir 18" dia., bears S.30°00'E., 47 lks. dist.

A Fir 10" dia., bears N.49°25'W., 45 lks. dist.

(Both trees blazed and scribed 1 H E S 140 BT.

The ¼ cor. of sec. 30, T29S R1W and sec. 25, T29S R2W, a stone mkd. and witnessed as described by the surveyor general bears S.89°12'E., 19.46 chs. dist.

Douglas Co. Surveyors Office - VR Tracy, Jack Heritage, & V. Perron, crew - Nov. 18, 1969 - C.S. File 54/96-1

-----

Found - No trace of old corner stone.

Orig. 18" now 28" Fir, sawed stump, S.30°E., 31.0 ft. We do not open.

Orig. 10" now 22" Fir, sawed stump, N.49¼°W., 29.7 ft., open and find scribe and reverse.

Set Brass cap at cor. mkd: County Surveyors Office

T 29 S R 2 W

Cor. #1 HES 140

1969

New BTs- 9" D.Fir N.6°E., 19.8 ft. mkd. "1 HES 140 CS BT"

8" D.Fir N.41½°W., 35.7 ft. "1 HES 140 CS BT".

This corner lies on northerly side of old, unused road in cut bank.

Fd. OK, Sept. 17, 1981 by L. Herzstein - C.S. File 61/27-46