

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 974040

PRIMARY CORNER DESCRIPTION Cor. No. 2, H.E.S. #140

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Homestead Entry Survey executed by Frank D. Maxwell, Forest Service, under Special Instructions dated April 27, 1914 - (DCSO records Vol. 27 Page(s) 11742)

Cor. No. 2, identical with Cor. H/2 of listing survey, a post, mkd. and witnessed as described by Asher Ireland, Asst. Forest Ranger, in place of which I
Set an igneous stone, 24x10x8 ins., 14" in the ground, for Cor. No. 2, mkd. 2 H E S 140 on NW. face, with a cross (X) on top; from which
A Pine 8" dia., bears N.11°10'E., 3 lks. dist.
A Fir 15" dia., bears S.28°25'E., 46 lks. dist., both trees blazed and scribed 2 H E S 140 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - Nov. 18, 1969 - C.S. File 54/96-2

Found - Old corner stone, in place, mkd. "+" on top and "2 HES 140" on North side.
Orig. 18" now 20" Pine, alive, N.11°E., 2.0 ft., shows scar, broken top 60 ft. up. We tag.
Orig. 15" now 28" Fir, alive, S.28½°E., 30.4 ft., shows good scar. Tag.

Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R 2 W
Cor. #2 / HES 140
1969

Reset stone alongside brass cap.
New BT - 14" Pine N.67°W., 14.2 ft. mkd. "2 HES 140 CS BT"
This corner lies on South edge of bench.

Fd. OK, Sept. 28, 1981 by L. Hersztein - C.S. File 61/27-56