

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 974050

PRIMARY CORNER DESCRIPTION Cor. No. 3 H.E.S. #140

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Homestead Entry Survey executed by Frank D. Maxwell, Forest Service, under Special Instructions dated April 27, 1914 - (DCSO records Vol. 27 Page(s) 11742-43)

-----  
To Cor. No. 3, identical with Cor. H/3 of listing survey, a post, mkd. and witnessed as described by Asher Ireland, Asst. Forest Ranger, in place of which I  
Set an igneous stone 24x13x7 ins., 14" in the ground, for Cor. 3, mkd. 3 H E S 140 on NE. face, with a cross (X) on top; from which  
    A Fir 11" dia., bears S.10°30'W., 20 lks. dist.  
    A Pine 11" dia., bears S.65°15'W., 31 lks. dist.  
Both trees blazed and scribed 3 H E S 140 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - Nov. 19, 1969 - C.S. File 54/96-5

-----  
Found - Old corner stone, in place, mkd. "+" on top and "3 HES 140" on N. side.  
    Orig. 11" now 24" Fir, alive, S.10½°W., 13.2 ft., shows good scar. Tag.  
    Orig. 11" now 38" Pine, alive, S.65¼°W., 20.5 ft., shows good scar. Tag.  
Set Brass cap at cor. mkd:           County Surveyors Office  
  T 29 S R 2 W  
  Cor. #3 | HES 140  
  1969  
Reset stone alongside.  
New BTs- 10" D.Fir N.32°W., 10.6 ft. mkd. 3 HES 140 CS BT.  
          12" D.Fir S.69°W., 9.2 ft. mkd. 3 HES 140 CS BT.  
This corner lies on gentle, southerly slope.

Fd. OK, Sept. 28, 1981 by L. Herzstein - C.S. Fle 61/27-55