

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 974060

PRIMARY CORNER DESCRIPTION Cor. No. 4 H.E.S. #140

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Homestead Entry Survey executed by Frank D. Maxwell, Forest Service, under Special Instructions dated April 27, 1914 - (DCSO records Vol. 27 Page(s) 11743)

Cor. No. 4, identical with Cor. H/4 of listing survey, a post, mkd. and witnessed as described by Asher Ireland, Asst. Forest Ranger, in place of which I
Set an igneous stone 24x14x7 ins., 14" in the ground for Cor. 4, mkd. 4 H E S 140 on SE. face, with a cross "X" on top; from which
 A Pine 11" dia., bears S.35°50'W., 72 lks. dist.
 A Fir 9" dia., bears N.88°50'W., 23 lks. dist.
Both trees blazed and scribed 4 H E S 140 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - Nov. 19, 1969 - C.S. File 54/96-6

Found - Old corner stone, in place, mkd. "+" on top and "4 HES 140" on E.
 Orig. 1" now 36" Pine, dead, S.36°W., 47.5 ft., shows faint scar.
 Orig. 9" now 18" Fir, alive, N.89°W., 15.2 ft., shows good scar. We rescribe "4 HES 140 CS BT" above old blaze.
Set Brass cap at cor. mkd: County Surveyors Office
 T 29 S R 2 W
 Cor. #4 /HES 140
 1969
Rese old corner stone alongside.
New BT - 12" D.Fir S.51°E., 32.3 ft. mkd. 4 HES 140 CS BT.
This corner lies on ridge top, course NE. and SW.

Fd. OK, Sept. 23, 1981 by L. Herzstein - C.S. File 61/27-52