TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 974070

PRIMARY CORNER DESCRIPTION Cor. No. 5 H.E.S. #140

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Homestead Entry Survey executed by Frank D. Maxwell, Forest Service, under Special Instructions dated April 27, 1914 - (DCSO records Vol. 27 Page(s) 11743)

Cor. No. 5, identical with cor. H/5 of listing survey, a post, mkd. and witnessed as described by Asher Ireland, Asst. Forest Ranger, in place of which I
Set an igneous stone 24x14x8 ins., 14" in the ground, for Cor. 5, mkd. 5 H E S 140 on SE. face, with a cross "X" on top; from which
A Fir 12" dia., bears S.82°00'W., 24 lks. dist.
A Fir 14" dia., bears N.45°00'W., 17½ lks. dist.
Both trees blazed and scribed 5 H E S 140 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - Nov. 19, 1969 - C.S. File 54/96-7

Found - Old corner stone, in place, mkd. "+" on top and "5 HES 140" on SE.
Orig. 12" now 21" Fir, alive, S.82°W., 15.8 ft., shows good scar. We rescribe "5 HES 140 CS BT"
Orig. 14" now 24" Fir, alvie, N.41°W., 11.6 ft. (Rec. N.45°W.) We tag.
Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R 2 W
Cor. #5 /HES 140
1969
Reset old stone alongside.
New BT - 14" D.Fir N.38°W., 8.0 ft. mkd. 5 HES 140 CS BT.
This corner lies on top of spur ridge, sloping SW.

Fd. OK, Sept. 30, 1981 by L. Herzstein - C.S. File 61/27-60