

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 975070

PRIMARY CORNER DESCRIPTION Cor. No. 8 H.E.S. #141

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Homestead Entry Survey executed by Frank D. Maxwell, Forest Service, under Special Instructions dated April 27, 1914 - (DCSO records Vol. 27 Page(s) 11752-53)

Cor. No. 8, on W. side of road exemption.
I set a wash boulder 24x10x10 ins., 14" in the ground, for Cor. 8, chiseled 8 H E S 141 on southerly face, with a cross (X) on top; from which
 A Fir 15" dia., bears N.88°00'W., 64 lks. dist.
 A Fir 12" dia., bears N.39°15'W., 63 lks. dist.
Both trees blazed and scribed 8 H E S 141 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V Perron, crew - Nov. 20, 1969 - C.S. File 54/96-13

Found - Old corner stone, buried, mkd. "+" on top and "8 HES 141" on South.
 Orig. 15" now 18" W.Fir snag, N.88°W., 42.2 ft., shows scar.
 Orig. 12" now 16" W.Fir snag, N.39¼°W., 41.6 ft., open and "H" scribe visible.
Set Brass cap at cor. mkd: County Surveyors Office
 T 29 S R 2 W
 Cor. #8 /\HES 141
 1969

Reset stone alongside.
New BTs- 10" Yew S.87°W., 55.1 ft. mkd. "8 HES 141 CS BT"
 18" Maple N.69°W., 22.5 ft. mkd. "8 HES 141 CS BT"
This corner lies on flat. Cor. #16 of same claim bears N.52°E., 41.9 ft.