

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 975080

PRIMARY CORNER DESCRIPTION Cor. #9 H.E.S. #141

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Homestead Entry Survey executed by Frank D. Maxwell, Forest Service, under Special Instructions dated April 27, 1914 - (DCSO records Vol. 27 Page(s) 11753)

-----  
I set an igneous stone 24x12x6 ins., 14" in the ground for Cor. 9, chiseled 9 H E S 141 on SW. face, with a cross (X) on top; from which  
    A Fir 12" dia., bears S.62°00'E., 127 lks. dist.  
    Fir 24" dia., bears S.58°45'E., 125 lks. dist.  
Both trees blazed and scribed 9 H E S 141 BT.

-----  
Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V Perron, crew - Nov. 21, 1969 - C.S. File 54/96-16

-----  
Found - No trace of old corner stone.  
    Orig. 24" now 32" Fir stump S.58 3/4°E., 82.5 ft., open and find "BT"  
    Orig. BT, pushed out of place about 50 ft. by cat, scribe visible.

Set Brass cap at cor. mkd:                   County Surveyors Office  
  T 29 S R 2 W  
  Cor. #9 | /HES 141  
  1969

New BTs- 20" Maple N.78°W., 12.0 ft. mkd. "9 HES 141 CS BT"  
          20" Cedar S.44°E., 62.5 ft. mkd. "9 HES 141 CS BT"  
This corner lies on S. side of old road, corner #15 of same survey bears N.55°E., 42.5 ft.