

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 975090

PRIMARY CORNER DESCRIPTION Cor. #10 H E S #141

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Homestead Entry Survey executed by Frank D. Maxwell, Forest Service, under Special Instructions dated April 27, 1914 - (DCSO records Vol. 27 Page(s) 11753)

-----  
Cor. No. 10, identical with Cor. H/5 of listing survey, a post, mkd. and witnessed as described by the listing surveyor, in place of which I  
Set an igneous stone 24x14x9 ins., 14" in the ground for Cor. 10, mkd. 10 H E S 141 on southerly face, with a cross (X) on top; from which  
    A Fir 20" dia., bears S.81°15'E., 63 lks. dist.  
    A Fir 36" dia., bears S.76°00'W., 21 lks. dist.  
Both trees blazed and scribed 10 H E S 141 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V Perron, crew - Nov. 21, 1969 - C.S. File 54/96-17

-----  
Found - Old corner stone, in place, mkd. "+" on top and "10 HES 141" on side.  
    Orig. 36" now 48" Fir, alive but dying, S.76°W., 13.9 ft., shows scar. We tag.  
    Orig. SE. BT, down, scar visible.  
Set Brass cap at cor. mkd:           County Surveyors Office  
  T 29 S R 2 W  
  Cor.#10 HES 141  
  1969  
New BTs- 8" W.Fir S.68°E., 6.1 ft. mkd. "10 HES 141 CS BT"  
          8" W.Fir N.1°E., 12.0 ft. mkd. "10 HES 141 CS BT"  
Cor. #14, same survey, bears N.2°W., 36.3 ft. (Rec. N.6°21'W., 32.0 ft.)