

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 975150

PRIMARY CORNER DESCRIPTION Cor. #15 Tract B HES 141

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Homestead Entry Survey executed by Frank D. Maxwell, Forest Service, under Special Instructions dated April 27, 1914 - (DCSO records Vol. 27 Page(s) 11755-56)

Set an igneous stone 24x10x7 ins., 14" in the ground for cor. 15, mkd. 15 H E S 141 on NE. face, with a cross (X) on top; from which

A Fir 20" dia., bears N.9°30'E., 31 lks. dist.

A Fir 16" dia., bears N.35°15'E., 79 lks. dist.

Both trees blazed and scribed 15 H E S 141 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - Nov. 1969 - C.S. File 54/96-22

Found - No trace of corner stone.

Orig. 20" Fir, now 36" Pine N.9½°E., 20.5 ft., alive, faint scar.

Orig. 16" now 30" W.Fir N.35¼°E., 52.1 ft., alive, we open and find scribe.

Set Brass cap at cor. mkd: County Surveyors Office

T 29 S R 2 W

Cor. #15 / _____ HES 141

1969

New BTs- 7" D.Fir S.35°E., 13.8 ft. mkd. "15 HES 141 CS BT"

14" W.Fir N.4°W., 33.5 ft. mkd. "15 HES 141 CS BT"

This corner lies SW. slope about 50 ft. from flat. Cor. #9, same HES bears S.55°W., 42.5 ft.