

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 975160

PRIMARY CORNER DESCRIPTION Cor. #16 Tract B HES 141

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Homestead Entry Survey executed by Frank D. Maxwell, Forest Service, under Special Instructions dated April 27, 1914 - (DCSO records Vol. 27 Page(s) 11756)

Cor. No. 16, identical with Cor. H/6 of listing survey, a post, mkd. and witnessed as described by the listing surveyor, in place of which I SET a wash boulder 24x10x8 ins., 14" in the ground for Cor. 16, chiseled 16 H E S 141 on S. face, with a cross (X) on top; from which
A Fir 24" dia., bears N.55°00'E., 77 lks. dist.
A Cedar 18" dia., bears S.71°00'E., 69 lks. dist.
Both trees blaze and scribed 16 H E S 141 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V Perron, crew - Nov. 20, 1969 - C.S. File 54/96-14

Found - Orig. 18" now 24" Cedar, alive, S.71°E., 45.5 ft. scribe visible. We rescribe "16 HES 141 CS BT"
Other orig. BT, down and badly decayed.
No corner stone found.

Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R 2 W
Cor. #16 | \ HES 141
1969

New BT - 11" W.Fir N.30°E., 24.0 ft. mkd. "16 HES 141 CS BT"
This corner lies on flat. Cor. #8, same survey, bears S.52°W., 41.9 ft.