

TOWNSHIP 29 RANGE 03E POINT IDENTIFIER # 100339

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 24 only, T29-2E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10693-4)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4
S 24 | S 19
1923

from which

- A fir, 36" dia., bears S.41°E., 12 lks., mkd: 1/4 S19 BT.
- A fir, 41" dia., bears N.43°W., 25 lks., mkd: 1/4 S24 BT.

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Group No. 64, surveyed May/Oct. 1927 - (DCSO) records Vol. 25 Page(s) 10772)

The 1/4 sec. cor. established for secs. 19 & 24, which is an iron post, 2" in dia., 10" above the ground, with brass cap mkd & witnessed as described in the field notes of the orig. survey, excepting the bearing of the west tree. I obliterate all marks on the E side of the brass cap and on BTs E of the line and mark new BTs W of the line from the cor.

- A pine, (new) 5" dia., bears S.67°W., 58 lks., mkd: 1/4 S24 BT.
- A fir, (old) 50" dia., bears N.73°W., 25 lks., mkd: 1/4 S24 BT.