

TOWNSHIP 29 RANGE 03E POINT IDENTIFIER # 100579

PRIMARY CORNER DESCRIPTION Cor Secs 1 & 12 only; T29-2E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated Dec. 21, 1920 - (DCS0 records Vol. 25 Page(s) 10696-7)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 1, 6, 7, & 12, with brass cap mkd

T29S  
R2E | R3E  
S 1 | S 6  
S 12 | S 7  
1926

from which

- A cedar, 30" dia., bears N.59½°E., 100 lks., mkd: T29S R3E S6 BT.
- A W.Fir, 12" dia., bears S.27°E., 57 lks., mkd: T29S R3E S7 BT.
- A W.Pine, 16" dia., bears S.19°W., 51 lks., mkd: T29S R2E S12 BT.
- A W.Fir, 20" dia., bears N.72°W., 37 lks., mkd: T29S R2E S1 BT.

GL0 survey by Herbert N Raymond, U.S. Cadastral Engineer, under Group No. 64, surveyed May/Oct. 1927 - (DCS0) records Vol. 25 Page(s) 10777)

-----  
The cor, established for secs. 1, 6, 7 & 12, which is an iron post, 2" in dia., 10" above the ground, with brass cap mkd & witnessed as described in the field notes of the orig survey. I obliterate all marks on E side of brass cap and on BTs E of line and remark brass cap as follows.

T29S  
S 1 | T29S  
S 12 | R3E  
R2E | S 7  
1926

This cor. will hereafter refer to secs. 1 & 12 only.