

TOWNSHIP 29 RANGE 03E POINT IDENTIFIER # 100639

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 1 only; T29-2E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10697)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4
S 1 | S 6
1926

from which

- A D.Fir, 14" dia., bears N.82°E., 35 lks., mkd: 1/4 S6 BT.
- A D.Fir, 24" dia., bears N.37°W., 30 lks., mkd: 1/4 S1 BT.

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Group No. 64, surveyed May/Oct. 1927 - (DCSO) records Vol. 25 Page(s) 10778)

The 1/4 sec. cor. established for seas. 1 & 6, which is an iron post 1" in dia., 11" above the ground, with brass cap marked & witnessed as described in the field notes of the orig. survey, I obliterated all marks on the E side of the brass cap and on the BTs E of the line, and mark a new BT W of the line, from the cor.

- A Fir, (old) 26" in dia., bears N.38°W., 31 lks., mkd: 1/4 S1 BT.
- A cedar, (new) 18" in dia., bears N.8°W., 73 lks., mkd: 1/4 S1 BT.