

TOWNSHIP 29 RANGE 03E POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29 & 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under special instructions dated Dec. 27, 1920, Surveyed June/Oct. 1927 - (DCSO records Vol. 25 Page(s) 10853)

-----  
Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for cor. of secs. 19, 20, 29, & 30, with brass cap mkd

T29S R3E  
S 19 | S 20  
S 30 | S 29  
1927

from which

- A cedar, 12" dia., bears N.43°E., 38 lks., mkd: T29S R3E S20 BT.
- A fir, 36" dia., bears S.44°E., 62 lks., mkd: T29S R3E S29 BT.
- A fir, 7" dia., bears S.39°W., 36 lks., mkd: T29S R3E S30 BT.
- A cedar, 16" dia., bears N.87°W., 94 lks., mkd: T29S R3E S19 BT.