

TOWNSHIP 29 RANGE 03E POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,  
under special instructions dated Dec. 27, 1920, Surveyed  
June/Oct. 1927 - (DCSO records Vol. 25 Page(s) 10856-7)

-----  
Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for  
cor. of secs. 17, 18, 19, & 20, with brass cap mkd

T29S R3E  
S 18 | S 17  
S 19 | S 20  
1927

from which

- A hemlock, 16" dia., bears N.88½°E., 76 lks., mkd: T29S R3E S17 BT.
- A fir, 48" dia., bears S.43°E., 46 lks., mkd: T29S R3E S20 BT.
- A fir, 40" dia., bears S.69°W., 7 lks., mkd: T29S R3E S19 BT.
- A fir, 44" dia., bears N.32°W., 40 lks., mkd: T29S R3E S18 BT.