

TOWNSHIP 29 RANGE 03E POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under special instructions dated Dec. 27, 1920, Surveyed June/Oct. 1927 - (DCSO records Vol. 25 Page(s) 10863)

-----  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 5, 6, 7, & 8, with brass cap mkd

T29S R3E  
S 6 | S 5  
S 7 | S 8  
1927

from which

- A fir, 30" dia., bears N.33½°E., 138 lks., mkd: T29S R3E S5 BT.
- A fir, 36" dia., bears S.51½°E., 86 lks., mkd: T29S R3E S8 BT.
- A fir, 32" dia., bears S.13½°W., 45 lks., mkd: T29S R3E S7 BT.
- A fir, 40" dia., bears N.38°W., 25 lks., mkd: T29S R3E S6 BT.