

TOWNSHIP 29 RANGE 03E POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,  
under special instructions dated Dec. 27, 1920, Surveyed  
June/Oct. 1927 - (DCSO) records Vol. 25 Page(s) 10838)

-----  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for  
cor. of secs. 28, 29, 32, & 33, with brass cap mkd

T29S R3E  
S 29 | S 28  
S 32 | S 33  
1927

from which

- A fir, 16" dia., bears N.12°E., 84 lks., mkd: T29S R3E S28  
BT.
- A fir, 9" dia., bears S.8°E., 29 lks., mkd: T29S R3E S33  
BT.
- A fir, 12" dia., bears S.55°W., 15 lks., mkd: T29S R3E S32  
BT.
- A fir, 12" dia., bears N.28°W., 120 lks., mkd: T29S R3E  
S29 BT.