

TOWNSHIP 29 RANGE 03E POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33 & 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,  
under special instructions dated Dec. 27, 1920, Surveyed  
June/Oct. 1927 - (DCSO) records Vol. 25 Page(s) 10826)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for  
cor. of secs. 27, 28, 33, & 34, with brass cap mkd

T29S R3E  
S 28 | S 27  
S 33 | S 34  
1927

from which

- A fir, 20" dia., bears N.44°E., 88 lks., mkd: T29S R3E S27  
BT.
- A fir, 14" dia., bears S.49°E., 79 lks., mkd: T29S R3E S34  
BT.
- A fir, 28" dia., bears S.71°W., 53 lks., mkd: T29S R3E S33  
BT.
- A fir, 34" dia., bears N.50°W., 9 lks., mkd: T29S R3E S28  
BT.