

TOWNSHIP 29 RANGE 03E POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Cor Secs 34, 35 and 2 & 3 T30-3E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,  
under Special Instructions dated Dec. 27, 1920 & Sept. 9,  
1927 - (DCSO records Vol. 25 Page(s) 10781)

-----  
Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for  
cor. of secs. 2, 3, 34, & 35, with brass cap mkd

T29S R3E  
S 34 | S 35  
S 3 | S 2  
T30S  
1927

from which

- A fir, 14" dia., bears N.31°E., 41 lks., mkd: T29S R3E S35  
BT.
- A fir, 10" dia., bears S.65½°E., 161 lks., mkd: T30S R3E  
S2 BT.
- A fir, 24" dia., bears S.69°W., 104 lks., mkd: T30S R3E S3  
BT.
- A fir, 28" dia., bears N.5°W., 22 lks., mkd: T29S R3E S34  
BT.