

TOWNSHIP 29 RANGE 03E POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,  
under special instructions dated Dec. 27, 1920, Surveyed  
June/Oct. 1927 - (DCSO) records Vol. 25 Page(s) 10816)

-----  
Set an iron post, 3 ft. long, 2" dia., 2" in the ground, for  
cor. of secs. 22, 23, 26., & 27, with brass cap mkd

T29S R3E  
S 22|S 23  
S 27|S 26  
1927

from which

- A fir, 8" dia., bears N.18°E., 416 lks., mkd: T29S R3E S23  
BT.
- A fir, 20" dia., bears S.39½°E., 249 lks., mkd: T29S R3E  
S26 BT.
- A cedar, 30" dia., bears S.39°W., 274 lks., mkd: T29S R3E  
S27 BT.
- A fir, 18" dia., bears N.2°45'W., 350 lks., mkd: T29S R3E  
S22 BT.