

TOWNSHIP 29 RANGE 03E POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under special instructions dated Dec. 27, 1920, Surveyed June/Oct. 1927 - (DCSO) records Vol. 25 Page(s) 10820-1)

-----  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 10, 11, 14, & 15, with brass cap mkd

T29S R3E  
S 10 | S 11  
S 15 | S 14  
1927

from which

- A fir, 30" dia., bears N.38°E., 65 lks., mkd: T29S R3E S11 BT.
- A fir, 18" dia., bears S.59°E., 36 lks., mkd: T29S R3E S14 BT.
- A fir, 30" dia., bears S.77°W., 102 lks., mkd: T29S R3E S15 BT.
- A fir, 28" dia., bears N.21°W., 20 lks., mkd: T29S R3E S10 BT.