

TOWNSHIP 29 RANGE 03E POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under special instructions dated Dec. 27, 1920, Surveyed June/Oct. 1927 - (DCSO) records Vol. 25 Page(s) 10804

Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for cor. of secs. 23, 24, 25, & 26, with brass cap mkd

T29S R3E
S 23|S 24
S 25|S 26
1927

from which

- A fir, 30" dia., bears N.38°E., 54 lks., mkd: T29S R3E S24 BT.
- A fir, 34" dia., bears S.40°E., 36 lks., mkd: T29S R3E S25 BT.
- A fir, 24" dia., bears S.23°W., 37 lks., mkd: T29S R3E S26 BT.
- A fir, 40" dia., bears N.43°W., 38 lks., mkd: T29S R3E S23 BT.

Harold L. Center, LS 1071 - For: Rogue River National Forest - 10/8/1986 - C.S. File 62/33-4

Section corner for Secs. 23, 24, 25 and 26

- Found - A 2½" claim. GLO monument properly marked in 1927.
- A 40" dia. Fir bears N.39°00'E., 36.1 ft. with a healed blaze.
 - A 48" dia. Fir bears S.40°51'E., 24.1 ft. with a healed blaze.
 - A 44" dia. Fir bears N.42°22'W., 25.4 ft. with a healed blaze. This tree is now dead and will be high-stumped during 1986 logging contract.

I stabilized the monument as needed and marked the following accessories:

- A 14" dia. Fir bears S.14°42'W., 18.9 ft. scribed T29S R3E S26 LS1071 BT.
- A 35" dia. Cedar bears N.27°53'W., 77.3 ft. scribed T29S R3E S23 LS1071 BT.