

TOWNSHIP 29 RANGE 03E POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under special instructions dated Dec. 27, 1920, Surveyed June/Oct. 1927 - (DCSO) records Vol. 25 Page(s) 10810-1)

-----  
Falls on a N edge of a level space, 3x3 ft. on a ledge, 20 ft. N & S 50 ft. E & W, and sloping W at this point.

Cut a (x) for the cor. of secs. 1, 2, 11, & 12, with 1 groove E & 5 grooves S of the cross, from which

A Twin Fir, 20" dia., bears N.55°E., 23 lks., mkd: T29S R3E S1 BT.

A fir, 14" dia., bears S.34°E., 60 lks., mkd: T29S R3E S12 BT.

A fir, 20" dia., bears S.83°W., 33 lks., mkd: T29S R3E S11 BT.

A fir, 22" dia., bears N.17°W., 173 lks., mkd: T29S R3E S2 BT.

Build a mound of stone, 3 ft. base, 1½ ft. high, 5 ft. S of the cor.