

TOWNSHIP 29 RANGE 03E POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Cor Secs 1, 2; 35, & 36 T28-3E

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under special instructions dated Dec. 27, 1920, Surveyed June/Oct. 1927 - (DCSO) records Vol. 25 Page(s) 10794-5 & Vol 24 pages 10465-6 duplicate)

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 1, 2, 35, & 36, with brass cap mkd

T 28 S R 3 E
S 35 | S 36
S 2 | S 1
T 29 S
1927

from which

- A larch, 20" dia., bears N.60°E., 43 lks., mkd: T28S R3E S36 BT.
- A larch, 22" dia., bears S.47°E., 46 lks., mkd: T29S R3E S1 BT.
- A larch, 18" dia., bears S.8°W., 19 lks., mkd: T29S R3E S2 BT.
- A larch, 10" dia., bears N.27°W., 36 lks., mkd: T28S R3E S35 BT.