

TOWNSHIP 29 RANGE 03E POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 12; 6 & 7 T29-4E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under special instructions dated Dec. 27, 1920, Surveyed June/Oct. 1927 - (DCSO) records Vol. 25 Page(s) 10792

Set an iron post, 3 ft. long, 2" dia., 12" in the ground, to a rock too large to be moved, and build a mound of stone, 4 ft. base, 1½ ft. high around the post, for cor. of secs. 1, 6, 7, & 12, with brass cap mkd

T 29 S
R 3 E R 4 E
S 1 | S 6
S 12 | S 7
1927

from which

- A larch, 10" dia., bears N.41½°E., 37 lks., mkd: T29S R4E S6 BT.
- A larch, 10" dia., bears S.22½°E., 85 lks., mkd: T29S R4E S7 BT.
- A larch, 14" dia., bears S.39°W., 36 lks., mkd: T29S R3E S12 BT.
- A larch, 12" dia., bears N.17°W., 55 lks., mkd: T29S R3E S1 BT.