

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 31 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by - Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 (DCSO records Vol. 15 Page(s) 6309)

Set ¼ sec. post, from which
 An Oak 8" dia., bears N.43°E., 92 lks. dist.
 An Oak 9" dia., bears N.1°E., 200 lks. dist.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13786)

Point for the ¼ sec.cor. of sec. 31 only, at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post 28" long, 2½" dia., 21" in the ground, with brass cap mkd.
 T 29 S
 ¼
 S 31
 R 3 W
 1964

from which
 A Fir 13" dia., bears N.81 ¾°E., 76 lks. dist. mkd. ¼ S31 BT.
 A Cedar 20" dia., bears S.41½°E. 84 lks. dist. mkd. ¼ S31 BT.