

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. cor. for 30 & 31 only, W. bdy.

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, under Contract #73, dated June 8, 1857 (DCSO records Vol. 15 Page(s) 6309)

Set post cor. secs. 30 and 31, from which
A Fir 12" dia., bears S.67°E., 21 lks. dist.
An Oak 12" dia., bears N.25°E., 123 lks. dist.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13787)

Point for the cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 28" long, 2½" dia., 21" in the ground, with brass cap mkd. T 29 S T 29 S

S 36	S 30
	S 31
	R 3 W
R 4 W	R 3 W
	1964

from which
A Cedar 10" dia., bears N.46 3/4°E., 65 lks. dist. mkd. T29S R3W S30 BT.

A Fir 27" dia., bears S.38°E., 92 lks. dist. mkd. T29S R3W S31 BT.

The corner is located at the edge of logged area, edge bears E. and W.

Fd. BC & 2 BTs by D.Edwards, 1/2009 - C.S. file 65/67-1 SET 6 ft. steel post 2' north

James Klein - For: Williams/Pacific Connector Gas Pipeline Project - 7/2015 - M166-44 A-F

Found - 3¼" brass cap stamped BLM 1964
21" cedar with healed face & tag dated 9/64,
N.46°45'E., 42.9'

24" fir 6' tall stump, S.38°E., 60.7'
New - 11" fir with (scribed X BT) set tag dated 11/13
N.80°W., 3.75' to nail side center.