



TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 100347

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. Sec. 24 only, T29-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs -15" Cedar bears N.70°W., 25.9 ft. scribed ¼ S24 CS  
BT.  
16" Cedar bears N.25°W., 28.5 ft. scribed ¼ S24 CS  
BT.  
E-W fence 10 ft. North.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13791)

-----  
The ¼ sec.cor. of sec. 24 only, remonumented and recorded by Germond, in 1918, subsequently remoumented by Byron in 1960, with an iron post 1" dia., 18" above ground, firmly set, with properly mkd. brass cap  
from which the remains of the original SW. bearing tree:  
A burned Pine stump 46" dia., bears S.20°W., 210 lks. dist. with recent axe marks visible.  
and bearing trees mkd. by Germond:  
A sawed Fir stump 24" dia., bears N.28½°E., 21 lks. dist. mkd. CS on an open blaze.  
A stump hole, bears S.15 3/4°E., 77 lks. dist.  
and bearing trees mkd. by Byron:  
A Cedar 16" dia., bears N.71¼°W., 39 lks. dist. mkd. ¼ S24 CS BT on double blaze.  
A Cedar 18" dia., bears N.26¼°W., 43½ lks. dist. mkd. ¼ S24 CS BT.  
and a bearing tree not of record:  
A sawed Fir stump 30" dia., bears N.52½°W., 46 lks. dist. mkd. BT on bark blaze.  
Add the marks BLM to the brass cap.

Fd. and used in BLM survey by Roseberry and Jelley, under Group #'s 255, 701, 938 - surveyed July 1967/Oct. 1977 - (DCSO records, Vol. 39 Page 15855)