

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 18; & S. 13, T29-4

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6298)

Set ¼ sec. post, from which
A Red Fir 12" dia., bears S.45°E., 15 lks.
A Red Fir 12" dia., bears N.41°W., 10 lks.

GLO survey by W.H. Byars, Contract ##376 dated Jan. 22, 1881 "found all trees standing" - (DCSO records, Vol. 15 Pg.6316)

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13793)

Point for the ¼ sec. cor. of secs. 13 and 18, restored by the method of irregular boundaries; there is no remaining evidence of the original corner.
Set an iron post 28" long 2½" dia., 23" in the ground, with brass cap mkd.
T 29 S
¼
R 4 W R 3 W
S 13 S 18
1964

from which
A Fir 22" dia., bears S.4¼°E., 75 lks. dist. mkd. ¼ S18 BT
A Fir 25" dia., bears N.44°W., 49 lks. dist. mkd. ¼ S13 BT

BLM resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1503, surveyed Sept. 1989/April 1990 - (DCSO records Vol. 50 Page(s) 18968)

The ¼ sec. cor., monumented with an iron post 2½" dia., firmly set, projecting 8" above ground, with brass cap mkd. in 1964, from which the remains of bearing trees mkd. by Beck:
A Fir 26" dia., bears S.4¼°E., 75 lks. dist., with healed blaze.
A burnt Fir stump 24" dia., bears N.44°W., 49 lks. dist., with healed blaze and a metal cap.
and a new bearing tree:
A Fir 4" dia., bears N.8°W., 34 lks. dist. mkd. X at breast height and BT at the base.
Corner is located on a SE. slope, at the easterly edge of a clearcut logging area.

continued next page

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 18; & S. 13, T29-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1775, surveyed Aug./Sept.. 1995 - (DCSO records Vol. 52 Page(s) 19946-7)

From the ¼ sec. cor. of secs. 13 & 18, on the E. bdy. of the Tp., monumented with an iron post, 2½" diam., firmly set, projecting 8" above ground, with brass cap mkd.

T29S

¼

R4W R3W
S 13 S 18

1964

from which the remains of bearing trees mkd. by Beck

A root hole, bears S.4¼°E., 75 lks., with down fir alongside, 24" diam., no marks visible.

A sawed fir stump, 26" diam., bears N.44°W., 49 lks., with healed blaze.

and a bearing tree mkd. by Bedell

A fir, 6" diam., bears N.8°W., 34 lks., with partially healed double blaze.

and a new bearing tree

A fir, 7" diam., bears N.85½°E., 31½ lks., mkd. ¼ S18 BT.